



FICHA TÉCNICA

Láminas de acabado espejo

Carbone Stainless Steel

DESCRIPCIÓN

Lámina de acabado espejo de calibre #16 de 4 x 8 pies. Cada lámina tiene una cubierta de PVC de alta resistencia que protege el acabado. Para su uso en proyectos arquitectónicos, construcción y varios.

CÓDIGO

LE 4X8 #16

Marca: Carbone Stainless Steel

Tipo: AISI 304

Espesor: 1.5 mm

Norma de Fabricación: ASTM A240/480

Calibre: #16

Procedencia: Importado

Medidas: 4' x 8' (pies) - 1219.2 x 2438.0 (mm)

Acabado: Espejo No. 8

EMPRESAS CARBONE S.A.		Certificate No. 180206C0022			
Product PRIME COLD ROLLED STAINLESS STEEL SHEET					
Specification ASTM A240M-16a/A480M-16b					
Steel Grade 304		Finish N0.8		Protect	PE

Item No.	Heat No.	Product Description			Chemical Composition(%)									Tension Test			*01	*02	C/No	
		Dimensions	Quantity Pcs	Weight kgs	C	Si	Mn	P	S	Ni	Cr	N	0.2% Y.S.	T.S.	E.L.					
					X10 ⁻³	X10 ⁻²	X10 ⁻²	X10 ⁻³	X10 ⁻³	X10 ⁻²	X10 ⁻²	X10 ⁻³	MPa	%	HRB	°C/W.Q.				
Specification				Min.	70	75	200	45	30	800	1750	1050	1950	100	205	515	40	92	1040	
1	C33AT1702538	0.9 mm x 1,219.0mm x 3,048.0 mm	63	1,671	44	48	90	31	5	806	1816	60	289	656	56	79	1050	81		
2	C33AT1702164	1.2 mm x 1,219.0mm x 3,048.0 mm	61	2,157	53	52	86	33	3	809	1805	46	263	651	60	78	1050	82		
3	C33AT1702538	0.9 mm x 1,219.0mm x 2,438.0 mm	81	1,718	44	48	90	31	5	806	1816	60	289	656	56	79	1050	83		
4	C33AT1703575	1.5 mm x 1,219.0mm x 2,438.0 mm	25	827	46	48	92	32	3	812	1824	58	259	624	60	78	1050	30		
TOTAL:			230	6,373																

Remark

Note

*01 = Hardness Test
*02= Heat Treatment
*Gauge Length: 50mm

1 MPa=1 N/mm²=10bar=145psi=
10.2kgf/cm²

Visual Inspection(Surface) and Dimension Check : OK

Surveyor By	We hereby certify that material described herein has been manufactured and tested with satisfactory results in accordance with the requirement of the above material specification. The material described above has been found free of radiation by raw material supplier.	1.ISO 9001:2015 (No.01100056299) 2.PED/AD2000 (No.01202TWN/Q-050105) 3.ISO 14001:2004 (No.01104822096385) 4.OHSAS 18001:2007 (No.01113822096385)
N/A		