



FICHA TÉCNICA

Producto: **Láminas de Acero Inoxidable tipo 430 SS**

DESCRIPCIÓN: Lámina de acero inoxidable tipo 430 SS de acabado satinado No.4 de calibre #18 de 4 x 10 pies y un espesor de 1.2 mm. Para su uso en proyectos arquitectónicos, construcción y varios. Solo pueden ser usadas en interiores.

CÓDIGO: LS 430 #18

Marca: Carbone Stainless Steel

Espesor: 1.2 mm

Calibre: #18

Medidas: 4' x 10' (pies) - 1219.2 x 3048 (mm)

Acabado: Satinado No.4

Tipo: 430 SS

Norma de Fabricación: ASTM A240/480

Procedencia: Importado

EMPRESAS CARBONE S.A.				Certificate No. 181012C0059				
Product		Prime Cold Rolled Stainless Steel Sheet						
Specification		ASTM A240M-17/A480-17						
Grade		430		Finish	NO.4		Protect	PE

Item No.	Product Description			Chemical Composition(%)								Tension Test			*01	*02	C/No.
	Dimensions	Quantity Pcs	Weight kgs	C	Si	Mn	P	S	Ni	Cr	0.2% Y.S.	T.S.	E.L.	B1	HR		
				X10 ⁻³	X10 ⁻²	X10 ⁻²	X10 ⁻³	X10 ⁻³	X10 ⁻²	X10 ⁻²	MPa	%	HRB				
	Specification		Min. Max.	120	100	100	40	30	75	1600 1800	205	450	22		89		
1	1.5 mm x 1,219.0 mm x 3,048 mm	40	1,717	40	36	34	24	3	14	1620	316	486	30	OK	82	30	
2	1.2 mm x 1,219.0 mm x 3,048 mm	50	1,717	40	28	31	23	2	10	1600	357	490	30	OK	81	31	
3	0.9 mm x 1,219.0 mm x 3,048 mm	50	1,287	40	26	35	32	3	15	1640	336	520	27	OK	82	36	
4	0.68 mm x 1,219.0 mm x 3,048 mm	50	973	40	33	38	27	2	13	1610	312	492	30	OK	80	36	
5																	
6																	
7																	
8																	
9																	
TOTAL:		190	5,694														
Remark				Note													
				*01 = Hardness Test *02= Heat Treatment *Gauge Length: 50mm													
Visual Inspection(Surface) and Dimension Check : OK				1 MPa=1 N/mm²=10bar=145psi=10.2kgf/cm²													
Surveyor	By	We hereby certify that material described herein has been manufactured and tested with satisfactory results ip accordance with the requirement of the above material specification. The material described above has been found free of radiation by raw material supplier.								1.ISO 9001:2015 (No.01100056299) 2.PED/AD2000 (No.01202TWN/Q-050105) 3.ISO 14001:2004 (No.01104822096385) 4.OHSAS 18001:2007 (No.01113822096385)							
N/A																	