

### **Account Details**

| Account No.   | 31596_USS1_30_10               |
|---------------|--------------------------------|
| Account Name  | ABB PANAMA SALES, S.A.         |
| Address       | ABB PANAMA SALES, S.A.,        |
|               | BOULEVARD COSTA DEL ESTE       |
|               | FINANCIAL, PARK, TORRE 1, PISO |
|               | 19 OFICINA A, PANAMA, Panama,  |
|               | 00000, Panama                  |
| Sales Org.    | ABB IS United States           |
| Sales Channel | Other ABB                      |
| Currency      | USD                            |
| As on Date    | 29-07-2022                     |
|               |                                |

## Catalog No. THQL2130

# **Product Details**



## UPC: 783164012927

Details: Q Line circuit breakers are one-inch wide per pole, compact, thermal-magnetic devices designed for residential and commercial applications in load centers or lighting panels. All Q Line circuit breakers feature Quick-make / Quick-break mechanisms, common trip bars, and easy to spot trip indication to ensure safety and reliability. Q Line breakers can be ordered with auxiliary contact and shunt trip accessories, and can be ordered for use in HID applications. The THQL2130 breaker features 2 poles, an ampere rating of 30 A, an interrupting rating of 10kAIC, and a voltage rating of 120/240V.

#### **Product Details**

#### Details

| Catalog No.         | THQL2130                  | UPC               | 783164012927 |
|---------------------|---------------------------|-------------------|--------------|
| Description         | THQL 2 POLE               | GSA Compliance    | Yes          |
|                     | 120/240V 10K IC 30<br>AMP | Discount Schedule | R5           |
| Std. Package Weight | 0.650 LB                  | CCC               |              |
| Product Family      | R5E                       | Currency          | USD          |
| Restock Fee         |                           | Notes             |              |
|                     |                           | Package Qty.      | 1            |

| Customer Reference No. |   | Country of Origin | Dominican Republic |
|------------------------|---|-------------------|--------------------|
| Minimum Order Qty.     | 1 | <br>              |                    |

# Specifications

| neral Characteristics            |                           | Dimensions and Clas | ssifications |
|----------------------------------|---------------------------|---------------------|--------------|
| ategory                          | Q Line                    | UL File #           | E11592       |
| roduct Line                      | Q-Line (Plug-In)          |                     |              |
| O Schedule                       | R5                        |                     |              |
| nterrupting Capacity<br>Rating   | 10 kAIC                   |                     |              |
| oltage                           | 120/240 V                 |                     |              |
| rip Style                        | Non-Interchangeable       |                     |              |
| rame Type                        | Q-Line                    |                     |              |
| mperage                          | 30 A                      |                     |              |
| system Voltage                   | 120 Vac<br>120/240<br>Vac |                     |              |
| oles                             | 2                         |                     |              |
| rip Function                     | LI                        |                     |              |
| continuous Current<br>ated       | Standard                  |                     |              |
| 20 Vac Interrupting<br>ating     | 10 KAIC                   |                     |              |
| 20/240 Vac<br>nterrupting Rating | 10 KAIC                   |                     |              |
| uitable for Reverse<br>eed       | Yes                       |                     |              |
| ong Time                         | Fixed                     |                     |              |
| nstantaneous                     | Fixed                     |                     |              |
| rotective Relays                 | No                        |                     |              |
| urrent Metering                  | No                        |                     |              |
| pecial Markings                  | HACR                      |                     |              |

| GSA | Compliance |
|-----|------------|
|-----|------------|

Yes

# **Publications**

|                   |              |  | Publication Type  |
|-------------------|--------------|--|---|
| -<br>PDF (0.0 kb) | 03/01/2009   | 455C872-SH1  | Drawings-Outline and<br>Dimensional                                       |
|                   |              |  |   |
| PDF (3938.7 kb)   | 06/23/2022   | DET1023  | Application and<br>Technical  |
|                   | 00/00/0004   | AQ_THQL_2P_CA                                      | P_CA Drawings - CAD - 3D  |
|                   | PDF (0.0 kb) | PDF (0.0 kb) 03/01/2009 PDF (3938.7 kb) 06/23/2022 | PDF (0.0 kb) 03/01/2009 455C872-SH1<br>PDF (3938.7 kb) 06/23/2022 DET1023 |

by ABB go.abb/industrial.com

Created On: 29/07/2022