



## Account Details

**Account No.** 31596\_USS1\_30\_10  
**Account Name** ABB PANAMA SALES, S.A.  
**Address** ABB PANAMA SALES, S.A.,  
BOULEVARD COSTA DEL ESTE  
FINANCIAL, PARK, TORRE 1, PISO  
19 OFICINA A, PANAMA, Panama,  
00000, Panama  
**Sales Org.** ABB IS United States  
**Sales Channel** Other ABB  
**Currency** USD  
**As on Date** 29-07-2022

Catalog No. THQL2170

## Product Details



**UPC:** 783164099201

**Details:** Q Line circuit breakers are one-inch wide per pole, compact, thermal-magnetic devices designed for residential and commercial applications in load centers or lighting panels. All Q Line circuit breakers feature Quick-make / Quick-break mechanisms, common trip bars, and easy to spot trip indication to ensure safety and reliability. Q Line breakers can be ordered with auxiliary contact and shunt trip accessories, and can be ordered for use in HID applications. The THQL2170 breaker features 2 poles, an ampere rating of 70 A, an interrupting rating of 10kAIC, and a voltage rating of 120/240V.

## Product Details

### Details

<b>Catalog No.</b>	THQL2170	<b>UPC</b>	783164099201
<b>Description</b>	THQL 2 POLE 120/240V 10K IC 70 AMP	<b>GSA Compliance</b>	Yes
<b>Std. Package Weight</b>	0.635 LB	<b>Discount Schedule</b>	R5
<b>Product Family</b>	R5M	<b>CCC</b>	
<b>Restock Fee</b>		<b>Currency</b>	USD
		<b>Notes</b>	No standard price available. Book price displayed

<b>Customer Reference No.</b>		<b>Package Qty.</b>	1
<b>Minimum Order Qty.</b>	1	<b>Country of Origin</b>	Dominican Republic

## Specifications

General Characteristics		Dimensions and Classifications	
<b>Category</b>	Q Line	<b>UL File #</b>	E11592
<b>Product Line</b>	Q-Line (Plug-In)		
<b>GO Schedule</b>	R5		
<b>Interrupting Capacity Rating</b>	10 kAIC		
<b>Voltage</b>	120/240 V		
<b>Trip Style</b>	Non-Interchangeable		
<b>Frame Type</b>	Q-Line		
<b>Amperage</b>	70 A		
<b>System Voltage</b>	120 Vac 120/240 Vac		
<b>Poles</b>	2		
<b>Trip Function</b>	LI		
<b>Continuous Current Rated</b>	Standard		
<b>120 Vac Interrupting Rating</b>	10 KAIC		
<b>120/240 Vac Interrupting Rating</b>	10 KAIC		
<b>Suitable for Reverse Feed</b>	Yes		
<b>Long Time</b>	Fixed		
<b>Instantaneous</b>	Fixed		
<b>Protective Relays</b>	No		
<b>Current Metering</b>	No		
<b>Special Markings</b>	HACR		

GSA Compliance

Yes

## Publications

Title	Type of Doc.	Date	Publication No.	Publication Type
Q-Line Plug-In MCCB, 100A Frame 1-, 2-, or 3-Pole, Drawing 1-Page fully dimensioned outline drawing in .pdf format	PDF (0.0 kb)	03/01/2009	455C872-SH1	Drawings-Outline and Dimensional
Section 1 BuyLog: Load centers and circuit breakers Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line.	PDF (3938.7 kb)	06/23/2022	DET1023	Application and Technical
Q Line CAD Shell Files - 3D CAD shell file in .stp format	Unknown (14044.1 kb)	06/22/2021	AQ_THQL_2P_CAD_Shell	Drawings - CAD - 3D
70A 2P THQL BREAKER 10K @ 120/240V FOR USE WITH 125A GE METER STACKS THQL2170 - 2P 70A 10K Breaker for 125A Sockets Outline Drawing	PDF (226.3 kb)	01/20/2016	DEE-853	Drawings-Outline and Dimensional

by ABB

[go.abb/industrial.com](https://go.abb/industrial.com)

Created On: 29/07/2022